



**Cable pulling rods
WALLY**

The economic

Unroll and roll up "by hand"
Mixed guide head (also acting as an eyelet)

Fiberglass rod : the most powerful
Diameter 3 mm

Twisted polyester rod : the unbreakable
Diameter 4 mm



Code **WBASIC-FV330**



Code **WBASIC-P430**

Length: 30 meters
Weight: 1,1 kg
Dimensions: 385 x 300 x 70 mm

Rotating housing: with the housing, no more pulling rods that get tangled

- The cable pulling rod is stored in a compact housing, from where it unwinds effortlessly
- Very resistant to shocks, the housing is adapted to life on construction sites and effectively protects the cable pulling rod
- Easy to store and carry thanks to its handle
 - 1) Take the pulling rod out of the housing
 - 2) Insert it into the sheath
 - 3) Remove the pulling rod from the sheath
 - 4) Rewind by rotating the ring

The WALLY BASIC includes:

- the fiberglass or twisted polyester rod in the housing
- a mixed guide head
- a "funnel" wire puller to hook wires or cables and easily pull them into the conduit.

The expert

Dynamic housing: unrolls and rolls up with a simple push
"All-purpose" guide head

Fiberglass rod : the most powerful
Diameter 3 mm



Code WEXPERT-FV330

Twisted polyester rod : the unbreakable
Diameter 4 mm



Code WEXPERT-P430

Length: 30 meters
Weight: 0,95 kg
Dimensions: 290 x 150 x 60 mm

Dynamic housing: with the housing, no more pulling rods that get tangled

- The cable pulling rod is stored in a compact housing, from where it unwinds effortlessly
- Very resistant to shocks, the housing is adapted to life on construction sites and effectively protects the cable pulling rod
- Easy to store and carry thanks to its handle
 - 1) Unwind the pulling rod and insert it directly into the sheath
 - 2) Pull the rod out and wind it directly into the housing

The WALLY EXPERT includes:

- the fiberglass or twisted polyester rod in the housing
- a flexible guide head \varnothing 7 mm at one end and a pulling eyelet at the other
- two pulling eyelets
- a storage compartment for accessories.

WALLY BASIC and WALLY EXPERT: common accessories

COMFORT kit



Flexible guide head Ø 7 mm



Cable pulling grip Ø 6-9 mm



Pulling handle GRIP

Code **WCONF**

REPARATION kit



M5 threaded tips



Glue



Connections

For fiberglass

Code **WREP**

All accessories are also sold separately:

Pulling eyelet M5 (x10)	WOEIL10
Flexible guide head Ø 7 mm	WTETE07
Flexible guide head Ø 10 mm	WTETE10
Flexible guide head Ø 13 mm	WTETE13
Mixed guide head	WTETEMIX
GRIP (pulling handle)	WGRIP
Cable grip Ø 6 to 9 mm	WCHAUSS69
Tips M5 for Ø 3 mm (bag of 10)	WEMB10
Connections Ø 3 mm (bag of 10)	WRAC10
Glue (3g tube)	WCOLLE3
Spare fiberglass rod Ø 3 mm - 30 m	WAIG-FV330
Spare twisted polyester rod Ø 4 mm - 30 m	WAIG-P430



Eyelets



Flexible guide head Ø 10 mm



Spare pulling rod



Flexible guide head Ø 13 mm

Fiberglass pulling rods



Fiberglass pulling rods for passing cables through hollow walls, partitions, false ceilings, gutters and crawl spaces.

They are rigid and allow installation in the most difficult to access spaces and over long lengths by pushing or pulling the cable.

Available in 2 versions :

- WALLY STICK diameter 4 mm (**Code WSTICK04**)
- WALLY STICK diameter 6 mm (**Code WSTICK06**)



Each WALLY STICK includes:



10 fiberglass rods of 1 meter each with M5 male and female ends



1 guide head



1 mixed flexible guide head



1 magnetic guide head



1 guide head with ring



1 guide head with hook



1 "lasso" cable hook